



DEALER INFORMATION

Dealer:	City:	State:	PO:	Date:
End User (required for valid order):	City:	State:	Type:	

STANDARD FEATURES Click here for product details: codeblue.com/product/cb-1-s



Basic Unit Configuration

Code Blue 1-standard (CB 1-s), pedestal mount enclosure

Color and Graphics Options STANDARD (choose below) CUSTOM (call)

Finish Color (choose one)

Safety Colors: Safety Blue Safety Yellow Safety Red

Optional Colors: Gloss White Bright Silver Tiger Orange Midnight Blue Gloss Black

Dark Bronze Cardinal Red Medium Bronze British Racing Green

Pantone: # _____

Clear Coat enclosure (for additional protection - recommended for saltwater regions)

Graphics Text (choose one)

Emergency Assistance Help Point Police Courtesy Security Information [None]

4-Sided Graphics (2-sided graphics are standard)

Graphics Color (choose one)

Reflective White Reflective Black Reflective Blue Reflective Red

Reflective Green Reflective Yellow [None]

OPTIONAL FEATURES

Faceplate Opening Options

Opening

Speakerphone - IA4100 (analog) 1 Button (+\$925) 2 Button (+\$1025) 2 Button with Keypad (+\$1075)

Speakerphone - IP5000 (IP) 1 Button (+\$1375) 2 Button (+\$1510) 2 Button with Keypad (+\$1560)

No Phone - blank Lexan plate (units ordered w/o phone will not contain surge suppression)

IP5000 Battery Back-Up (when not using PoE power)

Clear Coat faceplate (for additional protection - recommended for saltwater regions)

Main Bezel

PUSH FOR HELP (+\$0) (standard) EMERGENCY (raised letters w/ Braille) (+\$10)

EMERGENCY/EMERGENCIA (raised letters w/ Braille) (+\$10) Custom Overlay / Graphics (call)

Communication Connection Options

None

Wired (standard) Line - Analog (IA4100) / Ethernet (IP5000)

Wireless GSM Digital Cellular (+\$1195) Other (call)

DISCLAIMER: Code Blue NightCharge® or equivalent UPS-style back-up highly recommended for wireless connections

Power

Line Power (standard)

NightCharge (requires 120V AC external power supplied to CB unit)

NOTE: A backup battery assembly is recommended when an IP speakerphone is connected to a non-PoE network switch.

Voltage

24V AC (+\$0) (standard) 120V AC (+\$300) 240V AC (+\$300) 277V AC (+\$300) 347V AC (+\$300)

Product details: www.codeblue.com/product/cb-1-s

SEE PAGE 2 FOR ADDITIONAL FEATURES



OPTIONAL FEATURES - CONT.

Accessories

- Overhead Camera Mount (painted to match unit) (camera not included)
- Active Venting Option
- Public Address (painted to match unit)
- AED Housing (defibrillator not provided)
- 1 Series 5.25" Blank Mounting Ring (painted to match unit)
- 1 Series 5.25" Blank Mounting Ring with Antenna Post (painted to match unit)
- 1 Series 16.5" Blank Mounting Ring (painted to match unit)

Fiber Modules (1 pair TX/RX)

For IA4100 Analog Speakerphone Option available with IA4100 analog speakerphones; not available with IP5000 IP speakerphones.

- Fiber (MM/ST) to FXS media converter with contact closure w/power supply

For IP5000 IP Speakerphone Option available with IP5000 IP speakerphones; not available with IA4100 analog speakerphones.

- KBC Fiber (MM/ST) to 10/100Mbps Ethernet media converter w/power supply
- Comnet Fiber (MM/ST) to 10/100Mbps Ethernet media converter w/power supply (Qty. 2)

Copper - Ethernet Converter Option available with IP5000 IP speakerphones; not available with IA4100 analog speakerphones.

- Ethernet over twisted copper pair modem w/power supply, Evo DSL (Qty. 2)
- Ethernet over twisted copper pair modem for NightCharge Units, Evo DSL (Qty. 2)