



1.0 GENERAL DESCRIPTION

- 1.1 The unit shall be a vandal-resistant communications device that is a multi-functional, freestanding pedestal constructed of carbon steel, model CB 5-s from Code Blue Corporation, no substitutions. It shall include a high quality, hands-free communications device illuminated by a high intensity faceplate light and a powerful combination blue beacon/strobe light that serves to easily identify it from a distance.

2.0 CONSTRUCTION

- 2.1 The unit shall be a cylinder constructed of ASTM A500 seamless carbon steel structural tube, schedule 20, 8.625" outside diameter x 0.25" thick wall, at a height of 114" and weigh approximately 220 lbs.
- 2.2 The unit shall have an internal anchor base plate that is MIG welded 2" above the base and fabricated with a minimum of 0.50" thick A-36 grade steel plate. It shall have a 4" diameter center hole for electrical conduit access. The base plate shall have three oblong holes on a 6" circular bolt pattern for attachment.
- 2.3 An access door measuring 15" H x 6.63" W will be placed 10" from the bottom of the base to provide access for mounting to the anchor bolts and connectivity to electrical facilities. The opening shall have a cover plate, which mounts flush and is the same steel and radius as the unit. The cover plate shall fit into the opening and have a weather-resistant gasket. The cover plate shall be held in place by two ¼-20 x 1" countersunk proprietary fasteners.
- 2.4 Tamper resistant proprietary fasteners manufactured for Code Blue Corporation shall be used. It shall not be possible to acquire the custom-designed bit from any other source.
- 2.5 A recessed opening shall be cut at a point beginning 37.38" above the bottom of the unit. The opening shall be 14" tall at the forward edge and 12.38" tall at the rear edge, creating a 25-degree angle from the horizontal and an arc of 160 degrees in the face.
 - 2.5.1 The opening shall be enclosed by a 7 gauge steel plate with a single opening for a communication device.

3.0 MOUNTING

- 3.1 The unit shall be mounted onto three anchor bolts that are set 0.50" above the concrete. Standard 0.75" x 24" galvanized steel anchor bolts, nuts and washers shall be supplied.
- 3.2 The concrete foundation shall measure 24" x 24" minimum and the anchor bolts shall protrude 6" from the foundation.



4.0 ELECTRICAL

- 4.1 All electrical components shall have a modular plug for easy service and replacement, and will be equipped with a fuse for protection from transient voltage conditions.
- 4.2 Requires 1 ampere at 24V AC.
- 4.3 Voltage options shall include: 12-24V AC/DC; 120, 240 and 277V AC.
- 4.4 The unit shall have the option for Power over Ethernet for connectivity to a VoIP network switch with 802.3af or 802.3at (minimum) capabilities. Requires the LS1000 or IP5000 phone for connectivity to ToolVox or SIP/IAX2 compatible VoIP system.

5.0 LIGHTS

- 5.1 LED Beacon/Strobe: It shall have a rating of no less than 270 Lumens/92 candela, a factory-set flash rate of up to 375 flashes per minute and be programmable. A deep blue UV-rated polycarbonate prismatic refractor shall surround the LED Beacon/Strobe and be used to distribute the light in a horizontal pattern for maximum brightness and visibility.
 - 5.1.1 The communication device shall be factory programmed to activate the LED Beacon/Strobe for the duration of a call.
 - 5.1.2 The LED Beacon/Strobe shall be 5.10" tall and 5.50" in diameter.
 - 5.1.3 Optional 0.25" steel round powder coated blue cage available to connect to the top with security screws to protect light from vandalism.
- 5.2 Faceplate light: LED will direct light onto the communications device and be vandal resistant.
 - 5.2.1 The opening shall measure 4.50" W x .50" H.
 - 5.2.2 The light shall have a lifetime of 100,000 hours and a rating of 100 Lumens.

6.0 COMMUNICATIONS

- 6.1 The unit shall have a speakerphone communication device.
 - 6.1.1 LS1000/LS2000 – VoIP: Refer to the **LS1000 and LS2000 Architect and Engineering Specification** for further information.
 - 6.1.2 IP5000 - VoIP: Refer to the **IP5000 Architect and Engineering Specification** for further information.
 - 6.1.3 IA4100 - Analog: Refer to the **IA4100 Architect and Engineering Specification** for further information.



Architectural & Engineering Specifications

- 6.2 EIA/TIA, ANSI, CSA and BICSI cabling or similar standards shall be adhered to for proper operation of devices connected to copper or fiber infrastructure.

7.0 FINISH

- 7.1 Four-coat paint process, with zinc-rich primer for corrosion resistance and baked-on polyurethane enamel for maximum gloss and shine.
- 7.1.1 Optional clear coating process available to provide additional environmental protection.
- 7.2 Substrate preparation shall be as required to comply with applicable ASTM impact and adhesion standards: D2794 Direct and Reverse Impact, D523 Gloss @ 60 Degrees, D3359B Cross hatch Adhesion, D1654 Corrosion Creep, D714 Scribe Blisters and D714 Field Blisters.
- 7.3 The finish shall be available in 7 standard colors: Safety Blue, Safety Red, Safety Yellow, Gloss White, Gloss Black, Dark Bronze and Bright Silver. Custom colors shall be available.
- 7.4 Minimum coverage thickness of 2.0 mils.

8.0 COMPLIANCE

- 8.1 Americans with Disabilities Act (ADA) compliant
- 8.2 UL 60950-1 and UL 2017 listed
- 8.3 NFPA 72 Chapter 24 (2010) compliant
- 8.4 Meets NEMA 4 requirements

9.0 GRAPHICS

- 9.1 Engineering grade reflective vinyl for high visibility and legibility.
- 9.2 Standard 3.25" tall and 30" long graphics text offerings: Emergency or Assistance.
- 9.3 Standard graphics color offerings: Reflective White, Reflective Blue, Reflective Black.
- 9.4 Custom text, length and color options shall be available.

10.0 OPTIONS

- Overhead Camera Mount
- 360° Public Address Speakers
- Second opening for directory listings, camera, card reader or other mounted device
- Decorative Top

Architectural & Engineering Specifications

- The light housing shall measure 30" H x 21.5" W and weigh approximately 20 lbs.

11.0 WARRANTY

- 11.1 The CB 5-s shall be warrantied against any defects in material and workmanship, under normal use, for a period of 2 years from date of installation. If system is found by manufacturer to be defective within the warranty period, manufacturer shall repair and/or replace any defective parts, provided the equipment is returned to manufacturer.

12.0 MANUFACTURER

- 12.1 The Manufacturer shall be Code Blue Corporation. 800-205-7186, 259 Hedcor Street, Holland, Michigan 49423. www.codeblue.com. THERE ARE NO EQUIVALENTS.