



## Product Description

A **wireless cellular** option is available for areas where phone lines are not available or trenching costs are prohibitive, and can route incoming and outgoing calls through a GSM wireless network. Check with your service providers to confirm GSM service availability.

**NOTE:** National GSM service providers in the United States are AT&T and T-Mobile. Additional providers may be available. Check [wirelessadvisor.com](http://wirelessadvisor.com) for listings in your area.


## Standard Features

- ✓ FXS interface
- ✓ Default: Loop current disconnects. Optional: Reorder/Repeating tones
- ✓ Line features for disconnect
- ✓ SMA antenna connector
- ✓ Three LEDs for operational status
- ✓ 12V DC power
- ✓ Supports 2G and 3G network standards: HSPA+/UMTS/EDGE/GPRS/GSM
- ✓ Quad-band GSM 850/900/1800/1900 MHz

## Sim Card

A 15x25mm SIM card must be ordered from your service provider and inserted into the GSM to tap into mobile networks and hold critical information.

Standard



## Technical Features

### Available for the:

- CB 1-e
- CB 1-s
- CB 1-w
- CB 4-u

### Dimensions

- **Length:** 6.5" (16.51 cm)
- **Width:** 4.3" (10.92 cm)
- **Depth:** 1.2" (3.05 cm)
- **Weight:** 15 oz. (0.43 kg)
- **Operational temperature:** -40°C to +60°C (-40°F to +140°F)

Note: Specifications subject to change without notice or obligation on the part of Code Blue Corporation.