



Product Description

The **S-1000 LED beacon/strobe** light provides powerful and energy efficient light, even in direct sunlight, offering high visibility and acting as a deterrent to potential crime.

Standard Features

- ✓ Suitable for indoor or outdoor use
- ✓ Polycarbonate refractor with prismatic design to distribute light in a horizontal pattern
- ✓ Easily integrates with any Code Blue speakerphone to flash upon contact closure

Technical Features

Available for the:

- CB 1-e
- CB 1-s
- CB 1-w
- CB 2-e
- CB 2-s
- CB 5-s
- CB 5-p

Specifications

- **Height:** 5.1" (12.95 cm)
- **Diameter:** 5.5" (13.97 cm)
- **Weight:** 2.2 lbs. (1 kg)
- **Power:** 12-24V AC/DC
- **Operating temperature:** -40°F to +158°F (-40°C to +70°C)
- **Lumens:** 270 (92 Candela)
- **Flash Modes:** 21
- **Flash Rate:** Up to 375 per minute

Compliance

- UL 2017 (as part of enclosure)
- IP56
- NEMA 4



Additional Options



Remote Beacon/Strobe

Wall or pole mount a light with our adapter bracket and heavy duty stainless steel mounting kit.



S-1050 Photocell LED Beacon/Strobe

This photocell version has a dawn/dusk transition delay of 15-30 minutes and a transient light acknowledgement delay of at least three minutes to conserve power for units equipped with the NightCharge® or Solar Array Module.



Note: Specifications subject to change without notice or obligation on the part of Code Blue Corporation.