



DEALER INFORMATION

Dealer:	City:	State:	PO:	Date:
End User (required for valid order):	City:	State:	Type:	

STANDARD FEATURES



Basic Unit Configuration

Code Blue 1-standard (CB 1-s), pedestal mount enclosure

Color and Graphics Options STANDARD (choose below) CUSTOM (call)

Finish Color (choose one)

Safety Colors: Safety Blue Safety Yellow Safety Red

Optional Colors: Gloss White Bright Silver Tiger Orange Midnight Blue Gloss Black

Dark Bronze Cardinal Red Medium Bronze British Racing Green

Custom Color*

*A physical color sample must be sent to Code Blue for matching. It must be painted or professionally printed and be at least 2x2" in size.

Clear Coat enclosure (for additional protection - recommended for saltwater regions)

Graphics Text (choose one)

Emergency Assistance Help Point Police Courtesy Security Information [None]

4-Sided Graphics (2-sided graphics are standard)

Graphics Color (choose one)

Reflective White Reflective Black Reflective Blue Reflective Red

Reflective Green Reflective Yellow [None]

OPTIONAL FEATURES

Faceplate Opening Options

Opening

Speakerphone - IA4100 (analog) 1 Button 2 Button 2 Button with Keypad

Speakerphone - IP5000 (IP) 1 Button 2 Button 2 Button with Keypad

No Phone - blank Lexan plate (units ordered w/o phone will not contain surge suppression)

IP5000 Battery Back-Up

Clear Coat faceplate (for additional protection - recommended for saltwater regions)

Main Bezel

PUSH FOR HELP (standard) EMERGENCY (raised letters w/ Braille)

EMERGENCY/EMERGENCIA (raised letters w/ Braille) Custom / Silkscreen (call)



Second Opening (Top)

Blank Stainless Steel Plate Directory

Camera Enclosure w/ Color IP Camera Custom Camera Cut-Out (call)

Clear Coat 2nd faceplate (for additional protection - recommended for saltwater regions)

Communication Connection Options

None

Wired (standard) Line - Analog (IA4100) / Ethernet (IP5000)

Wireless GSM Digital Cellular Other (call)

DISCLAIMER: Code Blue NightCharge® or equivalent UPS-style back-up highly recommended for wireless connections

Power

Line Power (standard)

NightCharge (requires 120V AC external power supplied to CB unit)

Power over Ethernet (PoE) Extractor (powers auxillary Code Blue equipment)

NOTE: A POE+ switch must be utilized when powering this unit with a POE+ Extractor.

Voltage (Select the voltage that will be available at the installation site)

24V AC (standard) 120V AC 240V AC 277V AC 347V AC

Product details: www.codeblue.com/1-series

SEE PAGE 2 FOR ADDITIONAL FEATURES



OPTIONAL FEATURES - CONT.

Accessories

- Overhead Camera Mount (painted to match unit) (camera not included)
- Active Venting Option
- Public Address (painted to match unit)
- AED Housing (defibrillator not provided)
- 1 Series 5.25" Blank Mounting Ring (painted to match unit)
- 1 Series 5.25" Blank Mounting Ring with Antenna Post (painted to match unit)
- 1 Series 16.5" Blank Mounting Ring (painted to match unit)