



1.0 GENERAL DESCRIPTION

- 1.1 The unit shall be a vandal-resistant, high quality, communications device, model LS2000 from Code Blue Corporation, no substitutions. It shall have a real time, non-open source, proprietary operating system. It shall have a single enclosure comprised of all electronics with hook-switch, handset and PCB components.

2.0 CONSTRUCTION

- 2.1 The speakerphone shall measure 8.5" W x 11.75" H x 5.48" D with six screw holes and weigh approximately 5.1 lbs.
- 2.2 The faceplate shall be constructed of 0.104" thick stainless steel with custom-designed, vandal-resistant hook-switch opening.
- 2.3 An 8.5" W x 11.75" H x 0.13" D rubber gasket shall be on the back of the faceplate.
- 2.4 Faceplate shall include a non-moveable, magnetic reed hook-switch to limit usage failure and a 0.8 lb. black ABS handset receiver attached by stainless steel armored cord and swivel for vandal-resistance.
- 2.5 An optional keypad shall be mounted via .50" stainless steel studs, locking washers and lock nuts.
- 2.6 An optional 25mm programmable ring lit piezoelectric button that contains no mechanical parts shall be mounted into the faceplate.
- 2.7 Aluminum stand offs and locking washers shall be utilized to mount conformal coated electronics. A molded plastic housing shall be secured with aluminum standoffs, locking washers and stainless-steel screws. Weatherproof modular connectors shall be utilized for external power, auxiliary, PAS control, communication, audio output connectivity.

3.0 FINISH

- 3.1 Faceplate shall have an optional four-coat paint process, with zinc-rich primer for corrosion resistance and baked-on polyurethane enamel for maximum gloss and shine.
 - 3.1.1 Optional clear coating process available to provide additional environmental protection.
- 3.2 Flush mount: It shall be stainless steel with a 4b brushed finish.
- 3.3 Surface mount: It shall be stainless steel with a 4b brushed finish.



4.0 PRODUCT FEATURES

- 4.1 The enclosure shall be capable of using interchangeable faceplates: no button, one button, keypad and one button with keypad.
- 4.2 Self-monitoring and fault reporting for loss of power, PAS amplifier/speakers (if attached), battery voltage and button, handset phone and keypad failure. Built-in scripting language provides advanced button and diagnostic report programming.
- 4.3 Fault reporting shall be by SNMP management system or by custom script for placing outgoing calls and message playback.
- 4.4 The unit will have capability for infinite account registrations for flexibility.
- 4.5 Security features include HTTPS with 10-minute login use timer, Transport Layer Security (TLS) redundant with HTTPS, VLAN and password protection.
- 4.6 Operational temperature shall be -40° to +70° Celsius (-40° to +158° Fahrenheit).

5.0 COMMUNICATION FEATURES

- 5.1 The handset phone shall have a 4GB memory capacity for the storage of phone numbers and audio messages and be capable of configuration from a central TFTP server or embedded web GUI.
- 5.2 The handset phone shall have an 8 Ohm line level audio output.
- 5.3 The unit shall have three Ethernet ports, one capable of being connected to a PoE network switch.
- 5.4 The handset phone shall be capable of both manual and auto-dial features.
- 5.5 The handset phone will be able to handle phone numbers with up to 255 digits each and have an instantaneous dialing speed depending on the network.
- 5.6 In-call commands via DTMF: speaker volume and microphone volume.
- 5.7 Codec support: G.711a (PCMA), G.711u (PCMU), G.722, G.729, GSM, L16, iLBC, Opus, Speex.
- 5.8 STUN client for NAT transversal.
- 5.9 UDP and TCP communication protocols.
- 5.10 Embedded web server.
- 5.11 DTMF inband/out of band/INFO.
- 5.12 Three auxiliary Normally Open (NO) input contact closures and three auxiliary NO output contact closures with programmable timing capability.
- 5.13 Customizable incoming call scripting.



Architectural & Engineering Specifications

5.14 Volume control and hang-up functionality from both the caller and operator sides.

6.0 ELECTRICAL

- 6.1 Power over Ethernet IEEE 802.3af (15.4 maximum wattage) and PoE+ IEEE 802.3at (25.5 maximum wattage).
- 6.2 12V DC @ 350mA for PoE and 600mA for PoE+.
- 6.3 Optional SLA/AGM battery backup, with up to 16 hours of talk time/standby.
 - 6.3.1 Non-volatile memory ensures programming is retained during power loss.

7.0 OPTIONS

- 7.1 The LS2000 FP0 shall have handset only.
- 7.2 The LS2000 FP1 shall have one 25mm programmable ring lit piezoelectric button for volume control. The button shall be labeled VOLUME CONTROL.
- 7.3 The LS2000 FP1K shall have one 25mm programmable ring lit piezoelectric button and a standard telephone keypad. The button shall be labeled VOLUME CONTROL.
- 7.4 The LS2000 FPK shall have a standard telephone keypad.
- 7.5 Handset cord length options: 14", 18", 24" 54"
- 7.6 Please refer to the associated Architect and Engineering Specification for the following equipment:
 - 7.6.1 Code Blue enclosure options for installation: Tower and Wall Mount
 - 7.6.2 Remote mount blue beacon/strobe

8.0 COMPLIANCE

- 8.1 NEMA 3S or 4 compliant when installed in NEMA compliant enclosure.
- 8.2 UL 60950-22 compliant when installed in a Code Blue Help Point®.
- 8.3 UL 62368-1 compliant when installed in a Code Blue Help Point®.

9.0 WARRANTY

- 9.1 The LS2000 shall be warrantied against any defects in material and workmanship, under normal use, for a period of 2 years from date of shipment. If system is found by manufacturer to be defective within the warranty period, manufacturer shall repair and/or replace any defective parts, provided the equipment is returned to manufacturer.



10.0 MANUFACTURER

10.1 The Manufacturer shall be Code Blue Corporation. 800-205-7186, 259 Hedcor Street, Holland, Michigan 49423. www.codeblue.com. THERE ARE NO EQUIVALENTS.